

PROFESSIONAL SURFACE FINISHING SYSTEM

TECHNICAL INFO

LEAK SEEK

DESCRIPTION

LEAK SEEK is used to check for leakages in gas, pipes, tires, valves etc. With its unique consistency it will discover leakages even under vertical use.

PROPERTIES

- Can be used on the smallest leakages.
- Low water content makes it possible to be used in cold conditions.
- Consistence that allows easy detection of tiny leakages.
- Use of nitrogen propellant provides non-flammable product.
- 100% active product (Nitrogen propellant).

FIELD OF APPLICATION

- Can be used in temperatures from -15°C to +50°C.
- For weld joints, screw joints, valves, slides, pipes under pressure, gas heating systems, threaded pipe fittings, control clock, camping gas, tires, air hoses, etc.

USER INSTRUCTIONS

- 1. Spray on spot to be examined.
- 2. Bubble information shows leakages immediately.



LEAK SEEK – LES – 7	Art.no. 30203	
Signature: JH	Date: 2022-03-02	
This product information is property of VEIDEC AB and is not to be forwarded to third persons without our agreement. The product information has been made out according to our experiences; the corresponding distributing company has to point out probable characteristics as to the use of the product as the application fields are often very different. The recommendations as to technical use are not binding and do not justify any contractual relationship and subsidiary obligations under the contract of purchase. They especially do not relieve the buyer from testing our product on his own as to the suitability for the designated field of application.		



PROFESSIONAL SURFACE FINISHING SYSTEM

LEAK SEEK

TECHNICAL DETAILS

Colour:	Colourless, ranging between clear – slightly		
	cloudy.	FEATURES	
Packaging:	400 ml active material. Art.no. 30203		
Odour:	Mild.	1098500	UP-AND-DOWN.
VOC (directive 2010/75/EU):	49,6 %		
Density (20°C):	1,04 g/ml	CERTIFICATE	S
Propellant agent:	Nitrogen (non-flammable)	SPEEN WORLD	
Shelf life (temp.) months (+5°C to +25 °C):	24 months.		GREEN WORLD
Temperature resist:	-15°C to +50°C	VOM N32	
Application & Surface temperature:	-15°C to +50°C (can temperature should not be below 0°C).	GREEN	
Certificates & Registrations:	GREEN WORLD, GREEN PROPELLANT.		GREEN PROPELLANT.
Others:	In compliance with the legal regulations, please see current Material Safety Data Sheet. <u>https://veidec.com/en/msds</u>	LESS CO2	
Here here the state of the second state of the	Grow the OD and a few MGDC wide a wed at have	•	

User Instruction:

Scan the QR-code for MSDS, video and other information.



LEAK SEEK – LES – 7	Art.no. 30203	
Signature: JH	Date: 2022-03-02	
This product information is property of VEIDEC AB and is not to be forwarded to third persons without our agreement. The product information has been made out according to our experiences; the corresponding distributing company has to point out probable characteristics as to the use of the product as the application fields are often very different. The recommendations as to technical use are not binding and do not justify any contractual relationship and subsidiary obligations under the contract of purchase. They especially do not relieve the buyer from testing our product on his own as to the suitability for the designated field of application.		