

FLEX LUBE X-TREME PTFE FREE

DESCRIPTION

Flex Lube X-treme PTFE Free, in the VEIDEC Green World product series, is a high-performance lubricant based on a special blend of synthetic oil and vegetable-based esters. With very good anti-corrosion properties and thermal stability. It is moisture repellant, and the low viscosity offers unique running characteristics.

Flex Lube X-treme PTFE Free is NSF H2 certified.

PROPERTIES

- Due to the high penetrating power, it breaks through the thickest layers of rust and dirt loosening rusted frozen joints even in difficult to reach places.
- Unique lubrication power due to the special mixture of synthetic oils and high-performance additives, to give lubrication very well comparable to PTFE.
- The product can be used at running machines, e.g. not only when machine stops.
- Even wire ropes can be treated with this lubrication.
- Offers slide protection and above all rust protection.
- Due to the excellent adhesiveness the economic effect can be stressed.
- Free from PTFE (PFAS) and silicone substances.
- Canister in bluemint® recycled steel and with a certified production method, carbon dioxide emissions are reduced by 64%, compared to conventional steel.
- Included in the Green World product series.
- Certified bioLPG propellant with CO2 reduction up to 90%, naturally produced via organic waste = Green Propellant.

FIELD OF APPLICATION

- Universal lubricant for
- locks, hinges, slides, instruments, paper and printing machines, firearms, mechanical parts, etc.
- internal chain bearings, toothed and worm gears.
- all kinds of joints and couplings, machines, and precision devices etc.
- A long-term lubricant for rolls and ball bearings.
- Can be used for cleaning and protecting all kinds of chains and wire ropes in order to ensure easy and smooth running.
- Penetrates even the narrowest gaps. It's also appropriate for door-locks, door-hinges, slide bars, brake bars etc.

USER INSTRUCTIONS

Remove at first soiling of the parts to be sprayed on and shake can before use. Best results on cleaned surfaces.



FLEX LUBE X-TREME PTFE FREE - FLF - 131

Art.no. 20124-20126

Signature: JH

Date: 2024-10-29

This document is the property of VEIDEC AB and is not to be forwarded to third persons without our agreement. The product information has been made out according to our experiences; the corresponding distributing company must point out probable characteristics as to the use of the product as the application fields are often very different. The recommendations as to technical use are not binding and do not justify any contractual relationship and subsidiary obligations under the contract of purchase. They especially do not relieve the buyer from testing our product on his own as to the suitability for the designated field of application.

FLEX LUBE X-TREME

PTFE FREE

TECHNICAL DETAILS

Packaging:	500 ml bluermint® tin can aerosol. Art.no. 20124 300 ml alu can aerosol. Art.no. 20125 100 ml alu can aerosol. Art.no. 20126
Color:	Transparent.
Odor:	Characteristic.
Propellant:	Propane/Butane
Base Oil	Special blend of synthetic oils (Group V) and vegetable-based esters.
Additives:	EP
PFAS:	No
Application & Surface temperature:	-10°C to +50°C
Temperature resist:	-20°C to +250°C
Density (20°C):	0,74 g/cm ³
VOC (directive 2010/75 EG):	36,5 % (269 g/l)
Shelf life (temp.+5°C to +25 °C):	36 months.
Readily biodegradable content:	89,4%
Accessories:	Can fix. Art.no 35912
Miscellaneous:	In compliance with the legal regulations, please see current Material Safety Data Sheet. https://veidec.com/en/msds
User instructions:	Scan the QR-code for MSDS, video and other information.



VEIDEC FEATURES



GREEN WORLD VEIDEC's product series with focus on the environment and health as well as quality.



GREEN PROPELLANT. Propellant with lower carbon dioxide net emission.



UP-AND-DOWN The aerosol can be used upside down.



Shake well before use.

CERTIFICATES/REGISTRATIONS



Registered at NSF, products meeting the criteria for use in or around food-processing areas: category H2
[VEIDEC NSF listing](#)



Evaluated by Sunda Hus, Assessment B.



Registered at BASTA.

Evaluated by BYGGVARUBEDÖMNINGEN Byggsvarubedömningen, Undviks.

FLEX LUBE X-TREME PTFE FREE - FLF - 131

Art.no. 20124-20126

Signature: JH

Date: 2024-10-29

This document is the property of VEIDEC AB and is not to be forwarded to third persons without our agreement. The product information has been made out according to our experiences; the corresponding distributing company must point out probable characteristics as to the use of the product as the application fields are often very different. The recommendations as to technical use are not binding and do not justify any contractual relationship and subsidiary obligations under the contract of purchase. They especially do not relieve the buyer from testing our product on his own as to the suitability for the designated field of application.