

FLEX LUBE

DESCRIPTION

Flex Lube is a lubricating oil that is moisture – repellent, rust – dissolvent, hydrophobic, with high penetration capacity and very good adhesiveness. Contains polytetrafluorethylen (PTFE).

Flex Lube is NSF H1 approved as lubricant, release agents, or anti rust films on equipment and machine parts in and around food processing areas.

Meets the requirements of Green World.

PROPERTIES

- Unique lubrication power due to the special mixture of oil and Teflon.
- The product can be used at running machines, e.g. not only when machine stops.
- Even wire ropes can be treated with this lubricant.
- Offers slide protection and rust protection.
- Due to the excellent adhesiveness the economical effect can be stressed.
- Green World classified.
- Green certified propellant with CO2 reduction up to 90%, naturally produced via organic waste = Green Propellant.

FIELD OF APPLICATION

- A long-term lubricant for greasing rolls and ball bearings.
- Furthermore internal chain bearings, toothed and worm gears.
- All kinds of joints and couplings, machines and precision devices etc.
- The product is used for cleaning and protecting all kinds of chains and wire ropes in order to ensure easy and smooth running.
- Penetrates even to narrowest gaps. It's also appropriate for door-locks, door – hinges, slide bars, brake bars etc.

USER INSTRUCTIONS

Remove at first soiling of the parts to be sprayed on and shake can well before use.



FLEX LUBE – FLL – 20

Art.no. 20122

Signature: JH

Date: 2022-02-11

This product information is property of VEIDEC AB and is not to be forwarded to third persons without our agreement. The product information has been made out according to our experiences; the corresponding distributing company has to point out probable characteristics as to the use of the product as the application fields are often very different. The recommendations as to technical use are not binding and do not justify any contractual relationship and subsidiary obligations under the contract of purchase. They especially do not relieve the buyer from testing our product on his own as to the suitability for the designated field of application.

FLEX LUBE

TECHNICAL DETAILS

Color:	Beige.
Packaging:	500 ml alu can aerosol: Art.no. 20122
Odor:	Characteristic.
Basic oil:	Mineral oil and synthetic oil.
Density (20°C):	0,78 g/ml
VOC (directive 2010/75/EU):	33,8 %
Shelf life (temp.) months (+5°C to +25 °C):	24 months.
Temperature resist:	-30°C to +250°C
Application & Surface temperature:	-10°C to +50°C
Certificate:	GREEN WORLD, GREEN PROPELLANT, NSF H1, BASTA, Sunda Hus C-, Byggarubedömningen.
Others:	In compliance with the legal regulations, please see current Material Safety Data Sheet. https://veidec.com/en/msds
User Instruction:	Scan the QR-code for MSDS, video and other information.



CERTIFICATES/REGISTRATIONS



GREEN WORLD, Has low impact on user and the environment.



GREEN PROPELLANT.



Flex Lube is registered by BASTA.



NSF; Category code H1. Reg. no: 140533. <http://www.nsf.com/USDA/letters/140533.pdf>



Sunda Hus, Assessment C-.



Accepted.

FEATURES



UP-AND-DOWN.

FLEX LUBE – FLL – 20

Art.no. 20122

Signature: JH

Date: 2022-02-11

This product information is property of VEIDEC AB and is not to be forwarded to third persons without our agreement. The product information has been made out according to our experiences; the corresponding distributing company has to point out probable characteristics as to the use of the product as the application fields are often very different. The recommendations as to technical use are not binding and do not justify any contractual relationship and subsidiary obligations under the contract of purchase. They especially do not relieve the buyer from testing our product on his own as to the suitability for the designated field of application.