

MULTI LUBE

DESCRIPTION

Multi Lube is a very thin, transparent and highly penetrative multi-purpose product; Moisture Remover, Lubricant, Protector, Cleaner, Penetrating Oil etc.

Multi Lube is NSF-registered as lubricant, release agents, or anti rust films on equipment and machine parts (H2) in and around food processing areas.

PROPERTIES

- It completely removes moisture, thus preventing loss of voltage and short circuits in electrical installations.
- Due to its exceptionally high penetrating power, it breaks through the thickest layers of rust and dirt loosening rusted frozen joints even in difficult to reach places.
- Its unique lubricating power provides precision lubrication wherever desired.
- It provides excellent protection by forming a thin, invisible, molecular film that seals off the metal surfaces preventing oxidation even in salty or corrosive environments.
- The film never dries off and does not need to be removed prior to welding, pressing, or other treatments.
- Multi Lube may be used on ferrous and non-ferrous metals even if previously painted.
- It removes light dirt from machines and polished surfaces while protecting them.
- Cleans rubber and synthetic materials and keeps them soft and supple.
- Prevents cracking, jamming and freezing.
- Green certified propellant with CO2 reduction up to 90%, naturally produced via organic waste = Green Propellant.

FIELD OF APPLICATION

- Start wet engines. Prevents current loss in plug leads, distributors, dynamos, regulators, starting motors, switches, lighting, etc.
- Prevents oxidation and corrosion of exposed contacts, cables, battery terminals, fuses, tools, etc.
- Protects plated parts, castings and bare metal.
- Lubricates arials, locks, hinges, seat slides, precision instruments, textile, paper and printing machines, fire arms and aeronautical and marine instruments.
- Quickly loosens rusted joints and assemblies, exhaust pipes, etc.

USER INSTRUCTIONS

Shake well before use.



MULTI LUBE – MUL – 52

Art.no. 20101, 20102

Signature: JH

Date: 2021-11-23

This product information is property of VEIDEC AB and is not to be forwarded to third persons without our agreement. The product information has been made out according to our experiences; the corresponding distributing company has to point out probable characteristics as to the use of the product as the application fields are often very different. The recommendations as to technical use are not binding and do not justify any contractual relationship and subsidiary obligations under the contract of purchase. They especially do not relieve the buyer from testing our product on his own as to the suitability for the designated field of application.

MULTI LUBE

TECHNICAL DETAILS

Color:	Yellow.
Packaging:	500 ml tin plate aerosol: Art.no. 20101 5 liter Eco Box: Art.no. 25102
Accessories:	Tap 5l/15l Eco Box: Art.no. 35204 Air Mix Multi Lube: Art.no. 15215-14
Odor:	Characteristic.
Basic oil:	Mineral oil
Density (20°C):	0,81 g/cm ³
VOC (directive 2010/75/EU):	81% and bulk 72,9%
Shelf life (temp.) months (+5°C to +25 °C):	48 months.
Temperature resist:	-20°C to +175°C
Certificates & Registrations:	NSF H2, BASTA, GREEN PROPELLANT.
Others:	In compliance with the legal regulations, please see current Material Safety Data Sheet. https://veidec.com/en/msds
User Instruction:	Scan the QR-code for MSDS, video and other information.



CERTIFICATES/REGISTRATIONS



NSF; Category code H2. Reg.
no: 140531.



Multi Lube is registered by
BASTA.



GREEN PROPELLANT.
(aerosol)

FEATURES



UP-AND-DOWN (aerosol).

MULTI LUBE – MUL – 52

Art.no. 20101, 20102

Signature: JH

Date: 2021-11-23

This product information is property of VEIDEC AB and is not to be forwarded to third persons without our agreement. The product information has been made out according to our experiences; the corresponding distributing company has to point out probable characteristics as to the use of the product as the application fields are often very different. The recommendations as to technical use are not binding and do not justify any contractual relationship and subsidiary obligations under the contract of purchase. They especially do not relieve the buyer from testing our product on his own as to the suitability for the designated field of application.