

PEARL EFFECT PLUS

DESCRIPTION

Pearl Effect Plus gives a temporary, easy cleaning effect for surfaces made of glass, ceramic, different coated surfaces of plastic and metals surfaces. The impregnation generates a thin film (millionth millimetre), that decreases the adhesion of dirt and deposits and lets water and other liquids easily pearl off.

PROPERTIES

- The visibility is improved considerably during rain, raindrops rolling off making the use of windshield wipers obsolete.
- Ice, dirt and insects on windscreens are easily taken away without effort. Even without cleaning products on treated surfaces.
- Is very effective for vehicles front & side windows, improves visibility and enhance road safety.
- Provides professional and long-lasting results.
- Ideal in bathrooms and restrooms with easy cleaning effect to glass, porcelain, tiles, plastics, chromed surfaces.
- To windows and frames on building with dirt low adherent to surface the rolling off water drops creates a self-cleaning effect. Ideal on places difficult to reach.

FIELD OF APPLICATION

- To vehicle front and side windows and some lacquered parts.
- Bathrooms and toilets to be used on glass, ceramic, plastic, metal and tiles.
- Can be used on solar panels, outdoor camera lenses, etc.
- To windows and frames on buildings with self-cleaning effect.

USER INSTRUCTIONS

The product contains alcohol, sensitive surfaces can be harmed so compatibility has to be checked before usage.

1. Clean the surface to be treated with Super Foam, wipe the surface dry with Micro Gloss. For heavily soiled surfaces clean with ruff sponge and Bio Clean first, and then use Super Foam.
2. Rinse thoroughly with water and wipe the surface dry with Micro Gloss until it's completely dry and dust free.
3. Apply Pearl Effect Plus directly to the surface and polish it out lightly with a fluff-free cotton doth (use sparingly) until the surface is completely and evenly covered with Pearl Effect Plus.
4. Let it dry for at least 30 minutes (up to one day) in room temperature. In case of higher atmospheric humidity longer curing times are necessary.
5. After drying the grey film of surplus Pearl Effect Plus can be removed with a clean cotton cloth, ready!
6. If the easy-to-clean effect should diminish, a refresh can be preceded as with the first treatment.


PEARL EFFECT PLUS – PEP – 139
Art.no. 23103

Signature: JH

Date: 2022-01-04

This product information is property of VEIDEC AB and is not to be forwarded to third persons without our agreement. The product information has been made out according to our experiences; the corresponding distributing company has to point out probable characteristics as to the use of the product as the application fields are often very different. The recommendations as to technical use are not binding and do not justify any contractual relationship and subsidiary obligations under the contract of purchase. They especially do not relieve the buyer from testing our product on his own as to the suitability for the designated field of application.

PEARL EFFECT PLUS

TECHNICAL DETAILS

Color	Clear.
Packaging:	250 ml bag in valve aerosol system. Art.no. 23103
Odor:	Ethanol (alcohol).
Fully hardened time:	30 minutes to 24 h (depending on humidity and temp.)
Consumption (coverage):	5-10 ml/m ²
VOC (directive 2010/75/EU):	98,8 %
pH value:	5
Surface preparation:	Cleaned and dry surface.
Shelf life (temp.) months (+5°C to +25 °C):	24 months.
Application & Surface temperature:	+5°C to +40°C
Others:	In compliance with the legal regulations, please see current Material Safety Data Sheet. https://veidec.com/en/msds
Treatment duration:	The treated surface quality and effectiveness are mainly depending on how well the surface is cleaned before treatment, UV-light, distance and the frequency of windshield scraper use. If the easy-to-clean effect should diminish, a refresh can be preceded as with the first treatment
User Instruction:	Scan the QR-code for MSDS, video and other information.

FEATURES



UP-AND-DOWN.



PEARL EFFECT PLUS – PEP – 139

Art.no. 23103

Signature: JH

Date: 2022-01-04

This product information is property of VEIDEC AB and is not to be forwarded to third persons without our agreement. The product information has been made out according to our experiences; the corresponding distributing company has to point out probable characteristics as to the use of the product as the application fields are often very different. The recommendations as to technical use are not binding and do not justify any contractual relationship and subsidiary obligations under the contract of purchase. They especially do not relieve the buyer from testing our product on his own as to the suitability for the designated field of application.