

RUST SHOCK

DESCRIPTION

RUST SHOCK (chemical wrench) loosens screws, bolts and all rusted connections within a few seconds. Penetrates into the microscopic cavities and dissolves the rust crystals. Based on alcohol. NSF registered for use as a rust remover (P1).

PROPERTIES

- Extremely quick rust breaker, effective within 10-20 seconds.
- Does not contain any mineral oils, fats or silicone.
- Forms microscopic cavities through shock freezing.
- Quickly penetrates the microscopic cavities and dissolves the rust crystals.
- Time saver on can, you will save 15-20 minutes compared to traditional rust-removers.
- Does not leave a residue.
- Spray on surface, let it penetrate for 10-20 seconds, tighten and then loosen screw.
- Green certified propellant with CO2 reduction up to 90%, naturally produced via organic waste = Green Propellant.

FIELD OF APPLICATION

- Can be of help in hopeless cases.
- May be used on bolts, nuts, hinges, ball bearings and all joints that have rusted together.

USER INSTRUCTIONS

If possible, remove rust on surface with brush. Clean area to be treated with Power Clean or Soft Clean. Surface should be free from fat, grease, dirt and mud.



RUST SHOCK – RUS – 76

Art.no. 20205

Signature: JH

Date: 2021-11-10

This product information is property of VEIDEC AB and is not to be forwarded to third persons without our agreement. The product information has been made out according to our experiences; the corresponding distributing company has to point out probable characteristics as to the use of the product as the application fields are often very different. The recommendations as to technical use are not binding and do not justify any contractual relationship and subsidiary obligations under the contract of purchase. They especially do not relieve the buyer from testing our product on his own as to the suitability for the designated field of application.

RUST SHOCK

TECHNICAL DETAILS

Color shade:	Colorless.
Packaging:	500 ml alu can aerosol: Art.no. 20205
Odor:	Alcohol.
VOC (directive 2010/75/EU):	100%
Specific gravity:	0,78 g/cm ³
Shelf life (temp.) months (+5°C to +25 °C):	24 months.
Certificate/Registration:	NSF P1, GREEN PROPELLANT.
Others:	In compliance with the legal regulations, please see current Material Safety Data Sheet. https://veidec.com/en/msds
User Instruction:	Scan the QR-code for MSDS, video and other information.



CERTIFICATES/REGISTRATIONS



GREEN PROPELLANT.



NSF; Category code P1. Reg. no: 140537. <http://www.nsf.com/USDA/letters/140537.pdf>

FEATURES



UP-AND-DOWN.

RUST SHOCK – RUS – 76

Art.no. 20205

Signature: JH

Date: 2021-11-10

This product information is property of VEIDEC AB and is not to be forwarded to third persons without our agreement. The product information has been made out according to our experiences; the corresponding distributing company has to point out probable characteristics as to the use of the product as the application fields are often very different. The recommendations as to technical use are not binding and do not justify any contractual relationship and subsidiary obligations under the contract of purchase. They especially do not relieve the buyer from testing our product on his own as to the suitability for the designated field of application.