

SPRAY FIX

DESCRIPTION

Spray Fix is high quality glue based on synthetic resin for both permanent and temporary adhesion. Suitable to glue paper, cardboard, wood, textile and various types of plastic.

PROPERTIES

- Excellent for gluing large areas.
- Fast drying, easy to apply.
- Top quality glue for permanent or temporary jobs.
- Fast drying and easy to use.

FIELD OF APPLICATION

- Perfect for paper, card, wood, cork, textiles, plastics, leather, etc.
- Can also be used with porous material.

USER INSTRUCTIONS

The surface should be clean, dry and free of grease. For best result use Super Foam or Soft Clean. The aerosol should have room temperature.

1. Before use, shake the aerosol. Distance to the surface to be treated approximately 25 to 30 centimeter.
2. Apply the adhesive spray in an equal layer.
3. For a permanent adhesion treat both parts to be glued, allow to dry 15 to 20 minutes and firmly press together.
4. For a temporary adhesion treat one of the parts to be glued, allow drying for 5 to 10 minutes, and firmly pressing together. When treating porous surfaces, apply several layers.
5. After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

**SPRAY FIX – SFX – 87****Art.no. 15480**

Signature: JH

Date: 2021-12-28

This product information is property of VEIDEC AB and is not to be forwarded to third persons without our agreement. The product information has been made out according to our experiences; the corresponding distributing company has to point out probable characteristics as to the use of the product as the application fields are often very different. The recommendations as to technical use are not binding and do not justify any contractual relationship and subsidiary obligations under the contract of purchase. They especially do not relieve the buyer from testing our product on his own as to the suitability for the designated field of application.

SPRAY FIX

TECHNICAL DETAILS

Color:	Transparent white. Art.no: 15480
Packaging:	500 ml tin plate aerosol.
Odor:	Characteristic.
Full curing time:	Appr. 30 min
Density (20°C):	0,69 g/ml
VOC (directive 2010/75/EU):	87 %
Yield:	1,2 g/sec.
Shelf life (temp.) months (+20°C):	36 months.
Temperature resist:	-20°C to +80°C
Application & Surface temperature:	+15°C to + 25°C
Others:	In compliance with the legal regulations, please see current Material Safety Data Sheet. https://veidec.com/en/msds
User Instruction:	Scan the QR-code for MSDS, video and other information.

SYMBOLS



Shake well before use.



SPRAY FIX – SFX – 87

Art.no. 15480

Signature: JH

Date: 2021-12-28

This product information is property of VEIDEC AB and is not to be forwarded to third persons without our agreement. The product information has been made out according to our experiences; the corresponding distributing company has to point out probable characteristics as to the use of the product as the application fields are often very different. The recommendations as to technical use are not binding and do not justify any contractual relationship and subsidiary obligations under the contract of purchase. They especially do not relieve the buyer from testing our product on his own as to the suitability for the designated field of application.