

LEAK SEEK

DESCRIPTION

LEAK SEEK is used to check for leakages in gas, pipes, tires, valves etc. With its unique consistency it will discover leakages even under vertical use.

PROPERTIES

- Can be used on the smallest leakages.
- Low water content makes it possible to be used in cold conditions.
- Consistence that allows easy detection of tiny leakages.
- Use of nitrogen propellant provides non-flammable product.
- 100% active product.
- Included in the Green Line premium product range.

FIELD OF APPLICATION

- Can be used in temperatures from -15°C to +50°C.
- For weld joints, screw joints, valves, slides, pipes under pressure, gas heating systems, threaded pipe fittings, control clock, camping gas, tires, air hoses, etc.

USER INSTRUCTIONS

1. Spray on spot to be examined.
2. Bubble information shows leakages immediately.



LEAK SEEK – LES – 7

Art.no. 30203

Signature: JH

Date: 2025-11-25

This product information is property of VEIDEC AB and is not to be forwarded to third persons without our agreement. The product information has been made out according to our experiences; the corresponding distributing company has to point out probable characteristics as to the use of the product as the application fields are often very different. The recommendations as to technical use are not binding and do not justify any contractual relationship and subsidiary obligations under the contract of purchase. They especially do not relieve the buyer from testing our product on his own as to the suitability for the designated field of application.

LEAK SEEK

TECHNICAL DETAILS

Colour:	Colourless, ranging between clear – slightly cloudy.
Packaging:	400 ml bluemint® tin can aerosol ¹ . Art.no. 30203
Odour:	Mild.
VOC (directive 2010/75/EU):	49,6 %
Density (20°C):	1,04 g/ml
Propellant agent:	Nitrogen (non-flammable)
Shelf life (temp.) months (+5°C to +25 °C):	24 months.
Temperature resist:	-15°C to +50°C
Application & Surface temperature:	-15°C to +50°C (can temperature should not be below 0°C).
Others:	In compliance with the legal regulations, please see current Material Safety Data Sheet. https://veidec.com/en/msds
User Instruction:	Scan the QR-code for MSDS, video and other information.



VEIDEC FEATURES



GREEN LINE
Our premium product range with focus on the environment and health as well as quality



Registered at BASTA:



UP-AND-DOWN
The aerosol can be used upside down

¹ Canister in bluemint® recycled steel and with a certified production method, CO₂ emissions are reduced by 64%, compared to conventional steel.

LEAK SEEK – LES – 7

Art.no. 30203

Signature: JH

Date: 2025-11-25

This product information is property of VEIDEC AB and is not to be forwarded to third persons without our agreement. The product information has been made out according to our experiences; the corresponding distributing company has to point out probable characteristics as to the use of the product as the application fields are often very different. The recommendations as to technical use are not binding and do not justify any contractual relationship and subsidiary obligations under the contract of purchase. They especially do not relieve the buyer from testing our product on his own as to the suitability for the designated field of application.