

QUICK STOP

DESCRIPTION

QUICK STOP leak sealant has been produced to make quick repairs on leaking radiators and radiator systems. For smaller leaks the repairs may be permanent. It is a water based fluid that contains particles that inhibit the formation of lumps, an anti-corrosive agent and a lubricating agent.

PROPERTIES

- Seals leaks in radiators (metal and plastic) as well as in hair line cracks in gaskets, engine blocks and water pumps.
- Not only possible cracks and other leakages are closed but also leaky spots in hose couplings or hose bends in the whole radiator system resp. the radiator itself etc.
- The soft particles do not form lumps and therefore do not affect the cooling system.
- Protects the entire cooling system against rust and corrosion.
- Lubricates the water pump.
- The product is non-polluting and can be decomposed biologically.
- 1 bottle is suitable for approx. 20 litres coolant.

FIELD OF APPLICATION

- May be used in all kinds of coolers, and can be mixed with all types of glycol in petrol, diesel and LPG engines.
- Seals the water cooling circle system in an excellent way and the composition of the product prevents that neither metals, plastic materials nor rubber are corroded.
- NOTE: Not suitable for cooling circuits with a built-in filter unit.

USER INSTRUCTIONS

1. Fill system with water and glycol.
2. Warm up the engine slightly. (turn the control knob to get maximum heating into the passenger compartment).
3. Shake the Quick Stop bottle well and pour it in the expansion tank with the engine switched off.
4. Close the cooling system tightly, start the engine and keep it running until it reaches normal working temperature.
5. Check the fluid level.

Note:

It recommended draining the old coolant and flushing if the car is more than 50 000 km or more than 3 years old.

Be careful when opening the radiator / cooling system: hot coolant or steam might escape from the cooling system!



QUICK STOP – QST – 68

Art.no. 15501

Signature: JH

Date: 2023-05-09

This product information is property of VEIDEC AB and is not to be forwarded to third persons without our agreement. The product information has been made out according to our experiences; the corresponding distributing company has to point out probable characteristics as to the use of the product as the application fields are often very different. The recommendations as to technical use are not binding and do not justify any contractual relationship and subsidiary obligations under the contract of purchase. They especially do not relieve the buyer from testing our product on his own as to the suitability for the designated field of application.

QUICK STOP

TECHNICAL DETAILS

Color:	Brownish.
Packaging:	300 ml tin plate can. Art.no. 15501
Consumption:	1 can is good for 20 L.
Odor:	None.
Density (20°C):	1,02
pH:	Ca 7
VOC (directive 2010/75/EU):	0 %
Gap fill:	ca. <2,5 mm.
Shelf life (temp.) months (+20°C):	24 months.
Certificates & Registrations:	GREEN WORLD
Others:	In compliance with the legal regulations, please see current Material Safety Data Sheet. https://veidec.com/en/msds
User Instruction:	Scan the QR-code for MSDS, video and other information.

CERTIFICATES/REGISTRATIONS



GREEN WORLD

SYMBOLS



Shake well before use.



QUICK STOP – QST – 68

Art.no. 15501

Signature: JH

Date: 2023-05-09

This product information is property of VEIDEC AB and is not to be forwarded to third persons without our agreement. The product information has been made out according to our experiences; the corresponding distributing company has to point out probable characteristics as to the use of the product as the application fields are often very different. The recommendations as to technical use are not binding and do not justify any contractual relationship and subsidiary obligations under the contract of purchase. They especially do not relieve the buyer from testing our product on his own as to the suitability for the designated field of application.